

78969

Surge PIR 50W

FEATURES

- 3 years (2 years + 1 years) extended warranty
- Complete with built in Manual override PIR
- Constructed from die cast aluminium alloy & glass
- Matt black & clear glass finish
- IK07
- IP44

SPEC DATA

| | |
|------------------------|------------------|
| Product Wattage: | 50W |
| Product Lumen: | 4000 |
| Lumen/W: | 80 |
| Kelvin: | 4000K |
| Energy Rating: | A+ |
| Dimmable: | No |
| Beam Angle: | 110° |
| Operational Voltage: | 220-240V |
| Power Factor: | 0.9 |
| CRI: | 80 |
| Lifetime (Hours): | 25000 |
| SDCM: | 6 |
| Product Voltage: | 220-240V |
| Hertz: | 50/60 |
| Surge Protection (KV): | 1 |
| Operating Temp.: | -20 to 45 Degree |
| Product Weight (KG): | 0.95 |
| Cable Length (m): | 1m rubber cable |
| Class: | 1 |

PIR spec

| | |
|------------------|--------------------|
| LUX: | 2 - 2000 lux |
| Detection angle: | 120° |
| Maximum range: | 8±2m |
| Timer function: | 10±5 sec - 8±2 min |

Manual override function:

Switch unit on for over 3 seconds. Switch off and back on within 15 seconds. Unit then stays permanently on.

ACCESSORIES

- 61514, Inline IP68 connector tee IP68
- 61515, Inline IP68 connector straight IP68

