

Timers / **Hard Wired Timers**

Timer 7 Day Mechanical Socket Box Mounted



**Technical Specification**

|                     |                                                                                                        |
|---------------------|--------------------------------------------------------------------------------------------------------|
| Product Code        | T101A                                                                                                  |
| Feature 1           | Ideal for most heating applications                                                                    |
| Feature 2           | Timer ON status indicator                                                                              |
| Feature 3           | Fits 35mm dual appliance socket box should you require the timer next to a fused spur or socket outlet |
| Feature 4           | Will fit directly to any 35mm deep socket box fitted with an earth terminal                            |
| Ambient Temperature | 20                                                                                                     |
| Barcode             | 5012739638688                                                                                          |
| Battery Back Up     | N                                                                                                      |

|                                          |                                       |
|------------------------------------------|---------------------------------------|
| <b>Boost</b>                             | N                                     |
| <b>CE</b>                                | Y                                     |
| <b>Class Type</b>                        | II                                    |
| <b>Colour</b>                            | White                                 |
| <b>Company DUNS Number</b>               | 216156018                             |
| <b>Connections</b>                       | Wired                                 |
| <b>Country of Origin</b>                 | China                                 |
| <b>Current (I)</b>                       | R=16 L=2                              |
| <b>Display</b>                           | Mechanical                            |
| <b>Finish body</b>                       | Matt                                  |
| <b>Fixings supplied with product</b>     | N                                     |
| <b>Frequency (Hz) max</b>                | 50                                    |
| <b>Frequency (Hz) min</b>                | 50                                    |
| <b>Greenbrook Guarantee (Years)</b>      | 1                                     |
| <b>HS Code</b>                           | 9107000090                            |
| <b>Ingress Protection (IP)</b>           | IP20                                  |
| <b>Installation method</b>               | Flush mount                           |
| <b>Manual Override</b>                   | Y                                     |
| <b>Materials Main Body</b>               | Polycarbonate                         |
| <b>Maximum Load</b>                      | 16A for Immersion<br>Heaters upto 3kW |
| <b>Min Order Qty</b>                     | 1                                     |
| <b>No of Channels</b>                    | 1                                     |
| <b>Operating Temperature Range max C</b> | 40                                    |
| <b>Operating Temperature Range min C</b> | -10                                   |
| <b>Package Product Weight gross (g)</b>  | 159                                   |
| <b>Pollution Degree</b>                  | Normal                                |
| <b>Product (only) Max. Depth (mm)</b>    | 57.4                                  |
| <b>Product (only) Max. Height (mm)</b>   | 86.5                                  |
| <b>Product (only) Max. Width (mm)</b>    | 86.5                                  |
| <b>Product Weight net (g)</b>            | 126                                   |
| <b>Sales Pack Qty</b>                    | 1                                     |

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)

|                                |                                                 |
|--------------------------------|-------------------------------------------------|
| <b>Settings</b>                | 84 On / Off,<br>On/Timed/Off Switch<br>Selector |
| <b>Shortest Switching Time</b> | 2 hours                                         |
| <b>StatusCode</b>              | Active                                          |
| <b>Timer Switch Type</b>       | MICRO-<br>DISCONNECTION LIVE<br>POLE ONLY       |
| <b>UKCA</b>                    | Y                                               |
| <b>Voltage (VAC) MAX (V)</b>   | 240                                             |
| <b>Voltage (VAC) Min (V)</b>   | 220                                             |
| <b>Voltage (VAC) Rated (V)</b> | 230                                             |
| <b>Feature 5</b>               | 1 Year Guarantee                                |

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)