

Timers / Mechanical Timers

Timed Socket 24hr Mechanical White



Technical Specification

Product Code	TS70A
Feature 1	Simply replaces your normal socket with the added benefit of a timer application
Feature 2	To be fitted in plastic dry lining or plastic surface boxes
Feature 3	96 ON and OFF settings
Feature 4	Easy to set segments
Ambient Temperature	20
Barcode	5012739607776
Battery Back Up	N
Boost	N
CE	Y
Class Type	II

Tel No: 01279 772 772

Email: sales@greenbrook.co.uk

Website: www.greenbrook.co.uk

Colour	White
Company DUNS Number	216156018
Connections	Plug in with socket
Country of Origin	China
Current (I)	R=13 L=4
Display	Mechanical
Finish body	Matt
Fixings supplied with product	N
Frequency (Hz) max	50
Frequency (Hz) min	50
Greenbrook Guarantee (Years)	1
HS Code	9107000090
Ingress Protection (IP)	IP20
Installation method	Flush mount
Manual Override	Y
Materials Main Body	Polycarbonate
Maximum Load	13A Resistive Load 4A Inductive Load
Min Order Qty	1
No of Channels	1
Operating Temperature Range max C	40
Operating Temperature Range min C	.-5
Package Product Max. Length (mm)	155
Package Product Max. Height (mm)	55
Package Product Max. Width (mm)	94
Package Product Weight gross (g)	207.5
Pollution Degree	Normal
Product (only) Max. Depth (mm)	45.5
Product (only) Max. Height (mm)	146
Product (only) Max. Width (mm)	86.8
Product Weight net (g)	175
Sales Pack Qty	1

Tel No: 01279 772 772

Email: sales@greenbrook.co.ukWebsite: www.greenbrook.co.uk

Settings	84 On / Off, On/Timed/Off Switch Selector
Shortest Switching Time	2 hours
StatusCode	Active
Timer Switch Type	MICRO- DISCONNECTION LIVE POLE ONLY
UKCA	Y
Voltage (VAC) MAX (V)	240
Voltage (VAC) Min (V)	220
Voltage (VAC) Rated (V)	230
Feature 5	Manual override facility
Feature 6	Can be installed into PENC2G IP66 weatherproof twin enclosure
Feature 7	1 Year Guarantee